

DURO-LAST® PITCH PAN FILLER

DESCRIPTION:

Duro-Last® Pitch Pan Filler is an easy-flowing, self-leveling sealant for use in pitch pans and areas subjected to stress and vibration. The sealant is UV and impact resistant, non-staining, and is formulated for weather-tight adhesion to most types of building materials.

It is compatible with both Duro-Last PVC and Duro-TECH™ TPO membranes.

ORDERING:

Pitch Pan Filler is available in 10.1-ounce (299 ml) cartridges and can be ordered individually or in cases of 30.

One cartridge will cover approximately 18 in.³ (295 cm³).

- 10.1-ounce cartridge (Item #11222)

STORAGE AND HANDLING

- Store product out of direct sunlight, in a dry, cool, and well-ventilated place.
- Do not store in areas of ponding water.

Shelf Life

Shelf life of 12 months in an unopened tube at or below 80° F (27° C).

PRECAUTIONS:

- **KEEP AWAY FROM CHILDREN.**
- Use **only** in well-ventilated areas.
- Read Safety Data Sheets (“SDS”) prior to using. SDS can be found on the [Duro-Last website](http://duro-last.com).
- Wear proper personal protective equipment, such as gloves and eye protection, per the SDS.
- Avoid breathing vapors.
- Avoid repeated, prolonged contact with skin.



INSTALLATION:

1. General

- Do **not** apply to surfaces that bleed oils or solvents.
- Do **not** apply to surfaces that exceed 120° F (48° C).
- Do **not** use on Kynar®-coated metal or asphalt materials.
- Do **not** paint.

2. Preparation

- Pitch pans must be constructed of a rigid construction material such as:
 - Sheet metal
 - Wood
 - PVC pipe

3. Application

- Using mortar, concrete, or insulation:
 - Fill the pitch pan up to within 1/2 inch (13 mm) of the top ledge.
 - Take precaution to prevent the Pitch Pan Filler from migrating through the filler material.
 - Use an impervious material, such as Duro-Blue®, if required.
- Fill the entire top of the pitch pan with a minimum 1/2 inch (13 mm) of Pitch Pan Filler.
 - Apply using a standard caulking gun.
- Refer to appropriate details for complete installation instructions.
 - PVC Details 4030, 4040, and 4045
 - TPO Details T4030, T4040, and T4045

4. Cleanup

- Use mineral spirits for cleanup.

PITCH PAN FILLER PROPERTIES	
PROPERTY	DESCRIPTION
Color	White
Texture	Smooth
Volume	18 in. ³ (295 cm ³)
Cure Time	24 – 48 hours
Application Temperature	0° – 120° F (-17° – 48° C)
Low Temperature Flexibility	Retained to -40° F (-40° C)
UV Ratings ASTM G151	No change in appearance or physical properties after 2,000 hours of UV-A
Solubility	Not water soluble
	Soluble in most organic solvents