

DURO-LAST[®] POLY-PLATE

DESCRIPTION:

The Duro-Last[®] Poly-Plate is 0.335 inch (8.5 mm) thick, 2 inch (51 mm) diameter and manufactured using a glass-filled polycarbonate blend. Polycarbonate has proven weatherability and resiliency. Duro-Last Poly-Plates are packaged and sold in quantities of 1,000.

Duro-Last Poly-Plates include a recessed 0.280 inch (6.4 mm) diameter hole in the center to prevent the screw head from coming in contact with the Duro-Last[®] Roofing membrane. Duro-Last Poly-Plates have 10 “cleats” on the bottom to enhance the wind uplift characteristic of the Duro-Last membrane.

The Duro-Last Poly-Plate is a long-lasting and durable plate that is available only from Duro-Last, Inc.

MATERIAL SAFETY DATA SHEET:

Product Identity: Poly Plates

INSTALLATION:

The Poly-Plate is installed with the “cleats” toward the deck.

When used with prefabricated mechanically fastened systems, the Poly-Plate can be used for securing Duro-Last membranes to the deck along the prefabricated fastening tabs and the edges of the sheet parallel to the tab direction. The outside edge of the Poly-Plate must be installed flush to the edge of the fastening tab. Refer to detail 1190 for more installation information.

Do not use on the Duro-Roof[®] Roofing System prefabricated fastening tabs.

When used with adhered systems, the Poly-Plate must not be used for attachment of insulation or cover boards.

