

DURO-LAST[®] TERMINATION BAR

DESCRIPTION:

Duro-Last[®] Termination Bar (available in white, gray and tan colors) is fabricated from a rigid exterior vinyl with slotted holes 6 inches (152 mm) on center. Duro-Last Termination Bar may be used as perimeter detail for the Duro-Last roofing system and as termination on any square or rectangular penetration. Because of its symmetrical design, it is reversible.

Duro-Last Termination Bar is available in 10 ft. (3 m) lengths only. Duro-Last, Inc. will supply the termination bar in multiples of 10 ft. (3 m) and has two standard packages. The small tube package contains a maximum of 170 ft. (52 m) while a large box contains a maximum of 500 ft. (152 m).

MATERIAL SAFETY DATA SHEET:

Product Identity: 10 foot Extrusions

MSDS Number: 1225

INSTALLATION:

1. Duro-Last Termination Bar shall be fastened 6 inches (152 mm) on center with approved fasteners.
2. All termination bar must be fastened 1 inch (25 mm), maximum, from each corner or end of the bar.
3. The top edge of all sections of termination bar must be caulked.
4. It is necessary to leave a ¼ inch (6.3 mm) space between all sections of termination bar to account for expansion and contraction.
5. All vertical applications require caulk on both sides.
6. Refer to details 3010 & 3020 for installation information.

