

ADHESIVE COVERAGE RATES* **

	Γ	BEAD SPACING		NOTES
DURO-GRIP® PRODUCTS		12 INCHES O.C.	6 INCHES O.C.	
Insta-Stik [™]		800 sq. ft.	400 sq. ft.	Order 1 wand kit per every 3 tanks
TRU-FAST®		3,000 sq. ft.	1,500 sq. ft.	1 hose kit included per tank set
CR-20 (HFO)		3,300 – 3,500 sq. ft.	1,650 – 1,750 sq. ft.	1 hose kit included per tank set
OlyBond 500® (Bag in Box)	To concrete To insulation To smooth BUR To modified bitumen To gypsum To lightweight concrete To wood To steel	2,000 sq. ft. 2,000 sq. ft. 1,600 sq. ft. 1,600 sq. ft. 1,000 sq. ft. 1,500 sq. ft. 2,000 sq. ft. N/A	1,000 sq. ft. 1,000 sq. ft. 800 sq. ft. 800 sq. ft. 500 sq. ft. 750 sq. ft. 1,000 sq. ft.	Requires OMG [®] PaceCart
OlyBond 500 (SpotShot, 4/case)		400 – 600 sq. ft.	200 – 300 sq. ft.	Requires SpotShot Applicator
Millenium PG-1		See OlyBond 500 (Bag in Box) above		Requires Cyclone Applicator
Millenium One Step		See OlyBond 500 (S		
BAREBACK MEMBI	RANE PRODUCTS			
WB II	One-sided application	700 – 900 sq. ft. (900 sq. ft. for primed surfaces)		Use 9-inch medium nap roller
SB IV	Two-sided application	300 sq. ft.		Use 9-inch medium nap roller
Duro-Last Solvent-Grip®	Two-sided application	400 sq. ft.		Requires hose, spray gun and 2-foot extension

ADHESIVE COVERAGE RATES

		BEAD S	NOTES	
FLEECE MEMBRANE PRODUCTS		12 INCHES O.C.		6 INCHES O.C.
CR-20 (HFO)	Splatter method	2,700 – 3,000 sq. ft.		1 hose kit included per tank set
TRU-FAST®	Splatter method	2,400 sq. ft.		1 hose kit included per tank set
WB II	One-sided application	500 sq. ft.		Use 9-inch medium nap roller
Duro-Fleece® OMG	To concrete	2,000 sq. ft.	1,000 sq. ft.	Requires OMG PaceCart
(Bag in Box)	To insulation	2,000 sq. ft.	1,000 sq. ft.	
	To smooth BUR	1,600 sq. ft.	800 sq. ft.	
	To modified bitumen	1,600 sq. ft.	800 sq. ft.	
	To gypsum	1,000 sq. ft.	500 sq. ft.	
	To lightweight concrete	1,500 sq. ft.	750 sq. ft.	
	To wood	2,000 sq. ft.	1,000 sq. ft.	
Duro-Fleece OMG (SpotShot, 4-Case)		400 – 600 sq. ft.	200 – 300 sq. ft.	Requires SpotShot Applicator
OTHER PRODUCTS	3			
SureBond 240 (trowelable mastic)	One-sided application	450 sq. ft.		Requires trowel

^{*} Follow all installation guidelines for each respective adhesive manufacturer.

^{**} Coverage rates may vary.