

# KnuckleHead

## Rooftop Strut Support System



KnucklePads protect the roof membrane and reduce movement resulting from equipment vibration and wind

Strong, tough, weatherproof, UV stable, impervious to freeze-thaw cycles

Designed to support metal struts for installation of HVAC equipment and pipelines

Height is adjustable by rotating head – total height ranges from 3.2" - 5" depending on strut size

Each KnuckleHead is able to support up to 600 lbs.

Matte-finish nylon allows bonding with adhesive

Molded from *GREEN LINK* glass-reinforced nylon resin, which has metal-like properties

The Universal Base can be loose laid or attached using adhesive and/or screws\* to meet seismic and wind uplift conditions

\*When using screws, Duro-Last® stack flashings must also be used




800.248.0280 | [www.duro-last.com](http://www.duro-last.com)  
525 Morley Drive, Saginaw, MI 48601




# KnuckleHead

## Rooftop Strut Support System



Strut Supports are designed for a wide variety of applications including air conditioning units, solar panels, oversized pipes and other HVAC equipment that is to be installed on commercial roofs. Strut Supports are designed to accommodate standard metal struts which can provide a framework for keeping equipment elevated off the roof's surface. Each KnuckleHead can support up to 600 lbs. Units can be spaced to evenly distribute the load of the heaviest equipment. KnuckleHead extensions are available for raising roof-mounted pipes and equipment to higher elevations up to 18". Strut supports are lightweight, so they add little to total roof load, preventing low points and depressions that invite ponding water and ice build-up.

### Important points about The KnuckleHead Support System



**KnuckleHeads can help prevent damage to the membrane** caused by ponding water, wind, ice, flying debris or seismic events and protect the integrity of roof-mounted structures and equipment. GREEN LINK can custom cut metal strut, or design and manufacture special support elements such as a custom-molded base pad for a corrugated metal roof.

**They are engineered with a Universal Base** that can accommodate a range of head designs depending on the particular support application needed.

**KnuckleHeads can be loose laid or attached directly to the roof** either mechanically and/or with *Duro-Caulk® Advanced Sealant*.



**The Universal Base is designed with two holes at its center** for accepting mechanical fasteners. Before penetrating the roof membrane, the contractor should consult with the manufacturer to ensure that the warranty is not voided.

**Molded from tough, weatherproof polyurethane** and tinted safety yellow, slip-resistant KnucklePads can be placed under the KnuckleHead base to reduce movement and protect the roof membrane.

**Duro-Caulk® Advanced Sealant can be used by itself** to form a bond of up to 275 psi shear strength. This prevents movement of the supports caused by equipment vibration, high winds or seismic events.

**KnuckleHead installations have been performing in the field** for more than 15 years with continual exposure to high temperatures, freeze-thaw cycles, UV exposure and stress, and they have shown no signs of deterioration.

**A 10-year warranty** is available. Please contact GREEN LINK for details.



**GREEN LINK**  
ECO-ENGINEERING

800.248.0280 | [www.duro-last.com](http://www.duro-last.com)  
525 Morley Drive, Saginaw, MI 48601

**DURO-LAST**  
THE WORLD'S BEST ROOF®