

DURO-LAST SOLVENT-GRIP® CLEANER

DESCRIPTION:

Duro-Last Solvent-Grip® Cleaner is a low volatile organic compound (VOC) solvent cleaner used to clean Duro-Last Solvent-Grip Spray Adhesive hoses and spray guns. Duro-Last Solvent-Grip Cleaner is applied via a self-contained spray system.

- VOC Content: 0 g / L (EPA Method 24)
- Fast drying
- Not intended for use with any other adhesives or applications

ORDERING:

Duro-Last Solvent-Grip Cleaner is ordered individually. Each Duro-Last Solvent-Grip Cleaner cylinder can clean approximately 5 to 10 sets of hoses and spray guns.

- 15-pound cylinder (Item #11021)

STORAGE AND HANDLING

1. Protect Duro-Last Solvent-Grip Cleaner from freezing. If frozen, return to room temperature and agitate for 30 seconds before use.
2. Duro-Last Solvent-Grip Cleaner must not be shipped in temperatures less than -30° F (-34° C).
3. Store Duro-Last Solvent-Grip Cleaner between 50° F (10° C) and 90° F (32° C), out of direct sunlight, for maximum shelf life. Shelf life is one year in an unopened container, from date of manufacture printed on product, when following these recommended storage procedures.

Example: B05267-CL-10028
Date of Manufacture: 05/26/2017
Location: B, Batch: CL-10028



PRECAUTIONS:

1. Read Safety Data Sheets (SDS) prior to using.
2. Wear proper personal protective equipment, such as gloves and eye protection, per the SDS. **Goggles (glasses), gloves and impervious clothing are required.**
3. Combustible. Do not expose to heat, flame or sparks. Do not smoke while applying.
4. Use only in well ventilated areas and avoid breathing vapors.
5. Keep cylinder closed when not in use.
6. Treat empty cylinders with caution since they may contain flammable vapors.

APPLICATION:

1. General
 - a. Always keep the cylinder in an upright position. Attempting to dispense Duro-Last Solvent-Grip Cleaner when the cylinder is horizontal or upside down will cause only propellant to be released. Loss of propellant will significantly reduce the overall yield of the cylinder.
 - b. The hose and spray gun must not be allowed to dry out. Keep connected to the Duro-Last Solvent-Grip Spray Adhesive cylinder valve outlet and pressurized (valve open) until ready to clean. Refer to the Duro-Last Solvent-Grip Spray Adhesive Product Data Sheet for full instructions regarding that product.
 - c. Cleaning the hose and spray gun is not required if transferring to a new Duro-Last Solvent-Grip Spray Adhesive cylinder within two to three minutes.
2. Close the Duro-Last Solvent-Grip Spray Adhesive cylinder valve.
3. Depressurize the hose and spray gun by fully depressing the spray gun trigger until no more Duro-Last Solvent-Grip Cleaner flows from the gun.
4. Disconnect the hose and spray gun from the Duro-Last Solvent-Grip Spray Adhesive cylinder valve outlet using a 9/16-inch wrench.
5. Being careful to avoid cross-threading, connect the hose and spray gun to the Duro-Last Solvent-Grip Cleaner cylinder valve outlet.
6. Slowly turn the cylinder valve ON (counterclockwise rotation) and check for leaks at each attachment of the cylinder, hose and spray gun. Tighten accordingly to stop all leaks immediately. It is recommended to open the cylinder valve halfway initially. Use caution not to strip or overtighten any connection points.
7. Spray the Duro-Last Solvent-Grip Cleaner into a bucket until the hose and spray gun are clean. The spray gun operation will be smooth when completely cleaned.
8. If residual adhesive still remains, allow the hose and spray gun to rest under pressure for several hours to facilitate dissolving of the adhesive. Repeat Step 6.
9. Once cleaning is completed, close the Duro-Last Solvent-Grip Cleaner cylinder valve. Depressurize the hose and spray gun by fully depressing the spray gun trigger until no more Duro-Last Solvent-Grip Cleaner flows from the gun.
10. Disconnect the hose and spray gun from the Duro-Last Solvent-Grip Cleaner cylinder valve outlet using a 9/16-inch wrench.
11. Dispose of cleaners and waste materials properly. Never allow cleaners or waste materials to contact roofing materials.
12. Refer to the **DISPOSAL OF EMPTY CYLINDER** section of the Duro-Last Solvent-Grip Spray Adhesive Product Data Sheet for cylinder disposal instructions.



Hose to cylinder connection