

7.2 INSUL-RIB™ WALL PANEL

DESCRIPTION:



The 7.2 Insul-Rib™ Wall Panel combines a traditional 7.2 rib panel design with a premier polyurethane foam core. This panel can be installed both vertically and horizontally, allowing architects the same design flexibility that is available with our single skin 7.2 Panel.

FEATURES

- The 7.2 Insul-Rib Panel utilizes concealed clips and eliminates thermal short circuits.
- The 7.2 Insul-Rib Panel can be used for both interior and exterior applications.
- IMPs allow for fast assembly times and easy installation, resulting in reduced construction labor costs and earlier business starts.

SPECIFICATIONS

- Applications: Wall (Vertical or Horizontal)
- Coverage Widths: 36"
- Thicknesses: 3", 4", 5", 6"
- Lengths:
 - 8'-0" to 32'-0" for horizontal
 - 8'-0" to 40'-0" for vertical
- Panel Attachment: Offset double tongue-and-groove with extended metal shelf for positive concealed fastener face fastening
- Insulation Material: Non-CFC foamed-in-place polyurethane foam cured to achieve a minimum density of 2.2 pounds
- Gauges: Exterior: 26 24, 22; Interior: 26 24, 22
- Finishes: Exterior: Stucco-embossed; Interior: Stucco-embossed, Mesa profile
- Coatings: Signature® 200, Signature® 300, Signature® 300 Metallic



U-Factors and R-Values*

U-factor (BTU·h/ft²·° F)		R-Value (h·ft²·° F/BTU)	
PANEL WIDTH: 36"		PANEL WIDTH: 36"	
	75°		75°
3"	0.0814	3"	12.29
4"	0.0537	4"	18.62
5"	0.0395	5"	25.32
6"	0.0314	6"	31.85

* Based on ASTM C518, ASTM C1363 and thermal modeling, 75° F core mean temp.

Product samples, detail sheets, color chips, and color chart are available for your submittal package. For assistance with questions or submittals, contact your local Sale Representative or call Duro-Last.

Category	Test Method	Purpose	Result
FIRE US	ASTM E84	Surface Burning Characteristics of Building Materials	Flame spread <25, smoke developed <450
	ASTM E119	Fire Tests of Building Construction Materials	One hour non-load bearing rating with two layers of Type X Gypsum. Vertical or horizontal installation
	FM 4880	Class 1 Fire Rating of Insulated Wall, Ceiling and Roof Panels	Product approved Exterior roof requires FM 4881 approval
	NFPA 259	Test Method for Potential Heat of Building Materials	Potential heat of foam plastic insulation contained in the assembly tested in accordance with NFPA 285
	NFPA 285	Evaluation of Fire Propagation Characteristics of Exterior Non-Load Bearing Wall Assemblies	Panel assembly met the requirements of the standard
	NFPA 286	Fire Tests for Evaluating Contribution of Wall and Ceiling Finish to Roof Fire Growth	Test specimen met the criteria of the IBC Section 803.1.2.1
FIRE CANADA	CAN/ULC S101	Fire Endurance Tests of Building Construction and Materials	One hour non-load bearing fire rating with two layers of Type X Gypsum
	CAN/ULC S101	Fire Endurance Tests of Building Construction and Materials	Meets 15 minute stay-in-place requirements
	CAN/ULC S102	Surface Burning Characteristics of Building Materials and Assemblies	Meets the National Building Code of Canada requirements
	CAN/ULC S134	Fire Test of Exterior Wall Assemblies	Complies with the fire-spread and heat-flux limitations required by the National Building Code of Canada
	CAN/ULC S138	Fire Growth of Insulated Building Panels in a Full-Scale Room Configuration	Met the criteria of the standard
STRUCTURAL	ASTM E72	Strength Tests of Panels for Building Construction	See Load Chart
	ASTM E1592	Structural Performance of Metal Roof and Siding Systems by Uniform Static Air Pressure Differences	See Load Chart
	FM 4881	Class 1 Exterior Wall Structural Performance	See FM Wall Load Chart
THERMAL PERFORMANCE	ASTM C518	Steady-State Thermal Transmission Properties by Means of the Heat-Flow Meter Apparatus	K-Factor of 0.126 BTU.in/hr.ft ² °F at 40° F mean core K-Factor of 0.14 BTU.in/hr.ft ² °F at 75° F mean core
	ASTM C1363	Thermal Performance of Building Materials and Envelope Assemblies	See Thermal Performance Guide
AIR INFILTRATION	ASTM E283	Rate of Air Leakage Through Curtain Walls Under Specified Pressure Differences	<0.01 cfm/ft ² at 20 psf Vertical or horizontal installation
WATER INFILTRATION	ASTM E331	Water Penetration of Exterior Walls by Uniform Static Air Pressure Differences	No uncontrolled leakage when tested to a static pressure of 20 psf Vertical or horizontal installation
SPECIAL APPROVAL	State of Florida	Product Approval for the State of Florida	Product has State of Florida approval