

ATLAS® FR-10/FR-50 FIRE BARRIER SLIP SHEETS

DESCRIPTION:

Fire retardant coated mat (roof system component).

Features	Benefits
Proprietary coating	Flame-retardant mat
Tough and flexible	Handles wind and foot traffic
Product composition	Does not contribute to corrosion or mildew
Lines marked on roll	Easy alignment for overlapping
Convenient roll size	Easy to handle on the roof

INTENDED USE:

Thermal and fire barrier sheet listed by Underwriters Laboratories for use under Duro-Last roofing systems. FR-10/50 must be kept dry to retain its properties.

MATERIAL SAFETY DATA SHEET:

Product Name: Coated Glass Mat

INSTALLATION:

- FR-10/50 is part of a UL fire listed assembly when installed to meet Duro-Last roofing specifications.
- The slip sheet should be rolled out and overlap the preceding sheets a minimum of 2 inches (51 mm).
- On sloped applications or in windy conditions, use adequate fasteners and distribution plates to hold in place until the roofing membrane is installed.



GENERAL INFORMATION		
	FR-10	FR-50
Packaged	Roll	Roll
Length	250 ft. (76.2 m)	105 ft. (32 m)
Width	4 ft. (1.2 m)	4 ft. (1.2 m)
Coverage with 2-inch (51 mm) overlap	958 ft ² (89 m ²)	402 ft ² (37 m ²)
Roll weight	80 lb. (36.3 kg)	79 lb. (35.8 kg)
Weight per area	0.08 lb./ft ² (0.39 kg/m ²)	0.19 lb./ft ² (0.93 kg/m ²)