


T-EDGE ADVANCED

DESCRIPTION:

The T-Edge Advanced is designed with a double-folded drip edge neatly concealing the vinyl-coated hook strip so it is not visible from ground level. The system consists of three separate components: a drip edge, hook strip, and splice plate that are hooked together to form an aesthetically-pleasing edge.

- Fabricated in 10' lengths; 2" – 8" widths.
- Top piece consists of a vinyl-coated hook strip with a 6" attached PVC membrane skirt. Bottom drip edge piece available in any metal finish.
- Ready to assemble inside and outside corners are available.
- ANSI/SPRI ES-1 Compliant for 3" – 8" in 24-gauge galvanized and .040 aluminum.
- LEED® compliant.



INSTALLATION:

1. A wood nailer is required if 1" or greater of insulation is used.
2. Nailer should be attached to the wall in accordance with ANSI/SPRI ES-1.
3. Install in accordance with Duro-Last Detail #3555.
4. Any deviation from the requirements set forth in detail drawings must be pre-approved, in writing, by the Duro-Last Technical Department.

Material	Gauge	Finish
Aluminum	.040	Mill or Kynar®
Stainless Steel	24-gauge	N/A
Bonderized Steel	24-gauge	N/A
Galvalume®	24-gauge	Mill or Kynar®

WARRANTY:

Duro-Last offers a finish and substrate warranty.