

DURO-TECH LVOC SPLICE WASH CLEANER

DESCRIPTION:

Duro-TECH LVOC Splice Wash Cleaner ("Splice Wash Cleaner") is designed to clean and prepare Duro-TECH™ TPO membranes to be welded, or to receive primers, adhesives, or sealants, as noted in Duro-TECH specifications and details.

NOTE: This product is not intended for use with PVC or PVC KEE membranes.

ORDERING:

Splice Wash Cleaner is available in 3-gallon (11.4-L) pails.

- Duro-TECH LVOC Splice Wash Cleaner (Item #11022T)

Approximate coverage rates

- 200 – 250 ft²/gal (4.9 – 6.1 m²/L).

SHELF LIFE:

Shelf life of 2 years can be expected when stored in original, unopened container, at temperatures between 60° – 80° F (16° – 27° C).

PRECAUTIONS:

- **WARNING: EXTREMELY FLAMMABLE.**
Keep away from heat / sparks / open flames / hot surfaces.
- Keep away from ignition sources.
- **KEEP AWAY FROM CHILDREN.**
- **DO NOT SWALLOW.**
- Do not thin this product.
- Do not allow this product to come in contact with poly plates or plastic components.
- Use only outdoors or in well-ventilated areas.
- Read Safety Data Sheets (SDS) prior to using. SDS can be found at: <https://www.duro-last.com/>.
- Wear proper personal protective equipment, such as solvent-resistant neoprene gloves and eye protection with side shields, per the SDS.
- Avoid contact with eyes and skin.
- Avoid breathing vapors.
- Cover tightly when not in use.



STORAGE AND HANDLING:

- **WARNING: EXTREMELY FLAMMABLE.**
Keep away from heat / sparks / open flames / hot surfaces.
- Keep away from ignition sources.
- Store in original unopened container, out of direct sunlight, at temperatures between 60° – 80° F (16° – 27° C).

METHOD OF APPLICATION:

1. Ensure surfaces are clean, dry, and free of foreign materials and excess dust. Use a broom or rags to remove loose contaminants, if necessary.
2. Bring Splice Wash Cleaner to room temperature before applying.
3. Using clean cotton rags dampened with Splice Wash Cleaner, applying heavy pressure, move in circular motions over affected areas to remove contaminants.
4. Allow surfaces cleaned with Splice Wash Cleaner to dry completely (usually within 10 – 30 minutes).

TYPICAL PROPERTIES	
Properties	Value
Solvents	Solvent blend of acetone and mineral spirits
Viscosity	Very thin, free flowing
Weight/Gallon	6.6 lb/gal (790.9 g/L)
Weight	19.8 lb (9 kg)
VOC Content	< 2.1 lb/gal (< 250 g/L)