

PVC STANDARD FASTENER SPACING

Fastener Pullout Resistance	FASTENER SPACING IN. (MM) FOR BUILDING ROOF AREA LESS THAN 40-FT (12.2-M) TALL 60 LB/FT ² (292.9 KG/M ²) DESIGN								
	120-In. (3,048-mm) Rolls			60- or 64-In. (1,524- or 1,625.6-mm) Rolls			30- or 32-In. (762- or 812.8-mm) Rolls		
Pound-Force lbf (N)	Field In. (mm)	Perimeter* In. (mm)	Corner* In. (mm)	Field In. (mm)	Perimeter* In. (mm)	Corner* In. (mm)	Field In. (mm)	Perimeter* In. (mm)	Corner* In. (mm)
450 (2,001.7)	9 (228.6)	NA	NA	18 (457.2)	9 (228.6)	6 (152.4)	18 (457.2)	18 (457.2)	15 (381)
425 (1,890.5)	9 (228.6)	NA	NA	18 (457.2)	9 (228.6)	6 (152.4)	18 (457.2)	18 (457.2)	15 (381)
400 (1,779.3)	6 (152.4)	NA	NA	15 (381)	9 (228.6)	6 (152.4)	18 (457.2)	18 (457.2)	12 (304.8)
375 (1,668.1)	6 (152.4)	NA	NA	15 (381)	9 (228.6)	6 (152.4)	18 (457.2)	18 (457.2)	12 (304.8)
350 (1,556.9)	6 (152.4)	NA	NA	15 (381)	9 (228.6)	6 (152.4)	18 (457.2)	18 (457.2)	12 (304.8)
325 (1,445.7)	6 (152.4)	NA	NA	12 (304.8)	6 (152.4)	6 (152.4)	18 (457.2)	15 (381)	9 (228.6)
300 (1,334.5)	6 (152.4)	NA	NA	12 (304.8)	6 (152.4)	NA	18 (457.2)	15 (381)	9 (228.6)
275 (1,223.3)	6 (152.4)	NA	NA	12 (304.8)	6 (152.4)	NA	18 (457.2)	12 (304.8)	9 (228.6)
250 (1,112.1)	NA	NA	NA	9 (228.6)	6 (152.4)	NA	18 (457.2)	12 (304.8)	9 (228.6)
225 (1,000.9)	NA	NA	NA	9 (228.6)	NA	NA	18 (457.2)	9 (228.6)	6 (152.4)
200 (889.6)	NA	NA	NA	6 (152.4)	NA	NA	18 (457.2)	9 (228.6)	6 (152.4)
175 (778.4)	NA	NA	NA	6 (152.4)	NA	NA	15 (381)	9 (228.6)	6 (152.4)
150 (667.2)	NA	NA	NA	6 (152.4)	NA	NA	12 (304.8)	6 (152.4)	6 (152.4)
Less than 150 (667.2)	Contact the Duro-Last Engineering Services Department at 800-248-0280								

* Refer to the current ASCE 7 version for additional perimeter and corner width requirements.

DISCLAIMER

This document is meant as a quick reference and may not include details necessary for project completion. Please refer to the full Duro-Last specifications or contact the Duro-Last Engineering Services Department for additional information or assistance.